

## ROW Precision Balance

### General Specifications

- Display 22mm digit LCD display, with white LED backlight
- Capacities 3kg, 7kg, 15kg
- Pan size Ø232mm
- Keyboard 6 keys (Mechanical switch)
- Housing ABS plastic indicator
- Max. Divisions 30,000d; 70,000d; 150,000d
- ADC Sigma delta
- ADC update ≤ 1/10 second
- Operating Temp. 0°C ~ +40°C
- Power AC adapter (12V/500mA), Ni-MH battery (1.2V/2000mAh x 6)
- Gross weight 3.8kg



- Stainless steel pan
- An economical general purpose instrument
- Applications: 1. Net/gross shift 2. Weighing unit conversion 3. Check weighing
- Battery provides up to 40 hours of continuous use (without backlight)
- Standard RS-232 to connect to computer
- Optional initial-verification



## ROW Precision Balance

| Model Name | Capacity | Readability | Division | Approx. weight | Approval |
|------------|----------|-------------|----------|----------------|----------|
| ROW-3K     | 3kg      | 0.1g        | 30,000d  | 3.8kg          | CE       |
| ROW-7K     | 7kg      | 0.1g        | 70,000d  | 3.8kg          | CE       |
| ROW-15K    | 15kg     | 0.1g        | 150,000d | 3.8kg          | CE       |

### Options



### Dimensions(mm)

