



1



2



3

VCAP CE ISO 9001 OIML NTEP M

Features and Functions

- ◆Function keys: Tare, Units, Net/Gross, Print, Zero, On, Off
- ◆Weighing Mode, Counting Function, Checking Weight HI-OK-LO Function, Multiple Weighing Units Available
- ◆Power On Zero-Tracking, Auto-Calibration, Auto-Power Off mode, Digital Noise Filter, Full Tare, Accumulation Memory, Programmable Capacity, and Division, Low Battery Indicator and Charging Status Indicator

Specifications

- ◆Accuracy: III
- ◆Display: 23mm LCD display with LED backlit
- ◆Rechargeable battery 6V/4Ah for 120 hours continuous use
- ◆Power Supply: Input AC 100V-240V, Output 10V/600mA
- ◆Operating Environment: -10°C to 40°C (14°F to 104°F)
- ◆Platter: Stainless steel, Size:218mm*253mm
- ◆Product size: 308mmx250mmx97mm

Option

RS232 output and Relay output

Model	Capacity	Readability	Gross Weight	Division	CBM	Certificate
Q1W-3	3kg	0.05/0.1/0.2g	3.6kg	60000/30000 / 15000	38*38*15cm	CE
Q1W-6	6kg	0.1/0.2/0.5g	3.6kg	60000/30000 / 12000	38*38*15cm	CE
Q1W-15	15kg	0.2/0.5/1g	3.6kg	75000/30000 / 15000	38*38*15cm	CE
Q1W-30	30kg	0.5/1/2g	3.6kg	60000/30000 / 15000	38*38*15cm	CE
Q1W-3	1.5/3kg	0.5/1g	3.6kg	3000	38*38*15cm	CE&OIML&NTEP
Q1W-6	3/6kg	1/2g	3.6kg	3000	38*38*15cm	CE&OIML&NTEP
Q1W-15	6/15kg	2/5g	3.6kg	3000	38*38*15cm	CE&OIML&NTEP
Q1W-30	15/30kg	5/10g	3.6kg	3000	38*38*15cm	CE&OIML&NTEP